

Selection and Ordering data

Order No.

Echomax XLT-30, XLT-60, ultrasonic transducerTwo-wire connection, integral temperature sensor,
measuring range: min. 0.90 m, max. 30 m**XLT-30:** C) 7ML1141-**XLT-60:** C) 7ML1145-

E 0

Facing (standard)XLT-30¹⁾

0

XLT-60

1

XLT-30, nylon²⁾

2

XLT-60, nylon

3

Cable length

1 m

A

5 m

B

10 m

C

20 m

D

30 m

E

50 m

F

70 m

G

80 m

H

90 m

J

100 m

K

ApprovalsATEX II 2G 1D, CSA Class I Div. 1, FM Class I
Div. 2, CE 97

3

Instruction manual

Quick start manual, multi-language

C) 7ML1998-5QS81

Note: Due to ATEX regulations, one Quick start
manual is included with every transducer.

Applications Guidelines, multi-language

C) 7ML1998-5HV61

Note: The Applications Guidelines should be
ordered as a separate line item on the order.**Accessories**Tag, stainless steel with hole, 12 x 45 mm (0.47 x
1.77"), one text line for fastening on sensors

PBD-45000787

Easy Aimer II, NPT 1" Galvanized

7ML1830-1AP

Easy Aimer 304 with stainless steel coupling

7ML1830-1AU

Easy Aimer II, Aluminum with M20 adapter and 1"
and 1½" BSP aluminum couplings

7ML1830-1AX

1) 1" with XLT-60, XLT-30

2) 3" with XLT-60

C) Subject to export regulations AL: N, ECCN: EAR99