

Selection and Ordering data	Order No.
Low-pressure multiway cock for liquids and gases, for flanging to pressure transmitters, max. working pressure 25 bar, max. working temperature 60 °C (up to 80 °C for a short time), weight 1.75 kg (without accessory set)	7MF9004-4CA 7MF9004-4DA
Test connections 2x sealing screws G ³ / ₈ 2x quick-release couplings	

Selection and Ordering data	Order code	Order No.
Further designs¹⁾ Please add "-Z" to Order No. and specify Order code.		
Accessory set to DIN (required for flanging, weight 0.2 kg) 4x screws M10x25 to DIN EN 24017; chromized steel 4x washers Ø 10.5 mm to DIN 125; 2x gaskets made of PTFE, max. permissible temperature 80 °C <ul style="list-style-type: none"> • Standard design • Version for oxygen 	L11 7MF9004-6AD L15 7MF9004-6AE	
Accessory set to EN (required for flanging, weight 0.2 kg) 4x screws ⁷ / ₁₆ -20 UNF x 1 inch to ASME B18.2.1; chromized steel 2x gaskets made of PTFE, max. permissible temperature 80 °C		
Multiway cock in oil-free and grease-free design BAM-tested lubricant, gasket suitable for oxygen	S11	
Mounting bracket required for wall mounting or for securing on rack (72 mm grid), made of electrogalvanized sheet-steel, weight 0.85 kg	M13	7MF9004-6AA

¹⁾ When ordering accessory set or mounting together with the multiway cock, please use Order code; otherwise use Order No.