

Selection and Ordering data

Order No.

Easy aimer

Used on solids applications to aim transducers for optimal performance. Available in a 304 stainless steel model, or a cast aluminum model.

Easy Aimer 2, aluminum with M20 adapter and 1" and 1½" BSPT aluminum couplings

7ML1830-1AX

Easy Aimer 304, with M20 adapter and 1" and 1½" BSPT 304 SS couplings

7ML1830-1GN

Easy Aimer 2, aluminum, BSPT conduit

7ML1830-1AL

Easy Aimer 2, aluminum, without conduit

7ML1830-1AM

Easy Aimer 2, aluminum, NPT with 1½" galvanized coupling ¹⁾

7ML1830-1AN

Easy Aimer 2, aluminum, NPT with 1" galvanized coupling

7ML1830-1AP

Easy Aimer 2, aluminum, NPT with ¾" x 1" PVC coupling

7ML1830-1AQ

Easy Aimer 304, BSPT conduit

7ML1830-1AS

Easy Aimer 304, NPT with 1½" coupling ¹⁾

7ML1830-1AT

Easy Aimer 304, NPT with 1" coupling

7ML1830-1AU***Instruction manual***

Easy Aimer 2 and 304 Instruction manual, Multi-language

7ML1998-5HG62

Note: The instruction manual should be ordered as a separate line item on the order.

This device is shipped with the Siemens Milltronics manual CD containing the complete ATEX Quick Start and instruction manual library.

¹⁾ For use with XPS-30 or XPS-40 transducers only