



SITRANS F flowmeters

SITRANS F M

Transmitter MAGFLO MAG 6000 I/6000 I Ex d

Accessories MAG 6000 I

Description	Order No. ^{F)}	Symbol
Cable for standard electrode or coil, 3 x 1.5 mm ² /18 gage with shield PVC		
• 10 m (33 ft)	▶ FDK-083F0121	
• 20 m (65 ft)	▶ FDK-083F0210	
• 40 m (130 ft)	▶ FDK-083F0211	
• 60 m (200 ft)	▶ FDK-083F0212	
• 100 m (330 ft)	FDK-083F0213	
• 150 m (500 ft)	FDK-083F3052	
• 200 m (650 ft)	FDK-083F3053	
• 500 m (1650 ft)	FDK-083F3054	
Electrode cable for empty pipe or low conductivity, double shielded, 3 x 0.25 mm ² (cannot be used for Ex applications)		
• 10 m (33 ft)	FDK-083F3020	
• 20 m (65 ft)	▶ FDK-083F3095	
• 40 m (130 ft)	FDK-083F3094	
• 60 m (200 ft)	FDK-083F3093	
• 100 m (330 ft)	FDK-083F3092	
• 150 m (500 ft)	FDK-083F3056	
• 200 m (650 ft)	FDK-083F3057	
• 500 m (1650 ft)	FDK-083F3058	
Cable kit with standard coil cable, 3 x 1.5 mm ² /18 gage with shield PVC and electrode cable double shielded, 3 x 0.25 mm ²		
• 10 m (33 ft)	A5E01181647	
• 20 m (65 ft)	A5E01181656	
• 40 m (130 ft)	A5E01181686	
• 60 m (200 ft)	A5E01181689	
• 100 m (330 ft)	A5E01181691	
• 150 m (500 ft)	A5E01181699	
• 200 m (650 ft)	A5E01181703	
• 500 m (1640 ft)	A5E01181705	

▶ Available ex stock

Spare parts

Description	Order No. ^{F)}	Symbol
Display	FDK-085U3122	
Accessory bag including cable gland inserts coil & electrode connectors	FDK-085U3144	
Electronics cover with glass-plate Non Ex	7ME5933-0AC01	
Cover for connection board incl. gasket	7ME5933-0AC02	
Cover for connection board incl. gasket	7ME5933-0AC03	
Safety clamp	7ME5933-0AC06	

Complete spare part PCB unit

Description	Order No. ^{F)}	Symbol
Not Ex	FDK-085U3123	
MAG 6000 I Ex d 18 ... 30 V DC Spare PCB unit for use with ATEX sensors with increased safety e	A5E01013340	
MAG 6000 I Ex d 115 ... 230 V AC Spare PCB unit for use with ATEX sensors with increased safety e	A5E01013127	
Ex d version 18 ... 30 V DC for sensors with intrinsic safety ib 7ME633 and 7ME613 ≤ DN 300 (12")	FDK-085U3124	
Ex d version 115 ... 230 V AC for sensors with intrinsic safety ib 7ME633 and 7ME613 ≤ DN 300 (12")	FDK-085U3125	

Please use online Product selector to get latest updates.

Product selector link:

www.pia-selector.com/its_main_en.asp

Please also see www.siemens.com/SITRANSFordering for practical examples of ordering