

SITRANS TH100 temperature transmitters for Pt100

For installation in the connection head, Type B (DIN 43729)
Two-wire system 4 ... 20 mA, programmable, without electrical isolation

- | | | |
|--|---|-------------------------------------|
| • Without explosion protection | ► | 7NG3211-0NN00 ^{C)} |
| • With explosion protection, "Intrinsic safety" and for zone 2 | | |
| - to ATEX | ► | 7NG3211-0AN00 ^{C))} |
| - to FM (cFM _{US}) | ► | 7NG3211-0BN00 ^{C)} |

Further designs

Please add "-Z" to Order No. and specify Order code(s)

Order code

Customer-defined operating data

Y01

Test protocol (5 measuring points)

C11

Accessories

Order-No.

Modem for SITRANS TH100 and TH200 incl. SIPROM T parameterization software

- | | | |
|--------------------------|---|-----------------------------------|
| • with USB connection | ► | 7NG3092-8KU ^{C)} |
| • with RS 232 connection | ► | 7NG3092-8KM ^{C))} |

CD for measuring instruments for temperature

With documentation in German, English, French, Spanish, Italian, Portuguese and SIPROM T parameterization software

A5E00364512 ^{G)}

DIN rail adapters for head transmitters

(Quantity delivered: 5 units)

7NG3092-8KA

► Available ex stock.

C) Subject to export regulations AL: N, ECCN: EAR99.

G) Subject to export regulations AL: N, ECCN: 5D992B1.

Power supply units see "SITRANS I supply units and input isolators".