

Sensor SONO 3300 accessories and spare parts

Potting kit

Type/description	Order No. ^{F)}	Symbol
Potting kit, IP68, 10 m (32.81 ft) w.g. rating	FDK-085L2403	

Cables for FUS060

Type/description	Length m (ft)	Order No. ^{F)}	Symbol
Coaxial cable for FUS060, (75 Ω, max. 70 °C (158 °F), black PVC) (2 pcs.)	3 (9.84)	A5E00875101	
	15 (49.21)	A5E00861432	
	30 (98.43)	A5E01114226	
	60 (196.85)	A5E01114230	
	90 (295.28)	A5E01114231	
	120 (393.70)	A5E01114232	
High temp. coaxial cable for FUS060; with 0.3 m brown PTFE high temp. transducer part, max. 200 °C (392 °F) and black PVC for remaining transmitter part with SMB plug, max. 70 °C (158 °F); (impedance 75 Ω) (2 pcs.)	3 (9.84)	A5E00861438	
	15 (49.21)	A5E00861435	
	30 (98.43)	A5E01196342	

Cable connection boxes

Type/description	Order No. ^{F)}	Symbol
Junction box for coax cable	FDK-085B1361	
• IP68 metal box for 4 coax cables		

Cable glands (each 1 pc.)

Type	Material	Temperature range [°C (°F)]	Order No. ^{F)}	Symbol
PG 13.5	Chrome plated brass	-20 ... +100 (-4 ... +212)	FDK-085B1381	
PG 13.5	Stainless steel	-20 ... +200 (-4 ... +392)	FDK-085B1385	
M20	Plastic	-40 ... +100 (-40 ... +212)	FDK-085B1317	
M20	Chrome plated brass	-20 ... +100 (-4 ... +212)	FDK-085B1394	
M20	Stainless steel	-20 ... +200 (-4 ... +392)	FDK-085B1399	
½-NPT	½ Chrome plated brass	-20 ... +100 (-4 ... +212)	FDK-085B1319	

F) All products on this page subject to export regulations AL: 91999, ECCN: N.