Selection and Ordering data		Order No.
Valve manifolds for vertical differenting pressure lines for liquids and gases for flanging to pressure transmitters for lute and differential pressure Material: stainless steel, mat. No: 1.440 max. working pressure 420 bar (order accessory set with Order code)  • 3-spindle valve manifold  • 5-spindle valve manifold  Constructional and acceptance test Without certificate  With factory test certificate EN 10204-2  With material acceptance test certificate EN 10204-3.1	abso- 04/316L 2.2	1 D 1 E A B D
Selection and Ordering data	Order co	ode Order No.
Further designs <sup>1)</sup> Please add "-Z" to Order No. and specify Order code.		
Accessory set to DIN <sup>2</sup> ) (connection between valve manifold and pressure transmitter)  4x screws M10x45 to DIN EN 24014; chromized steel  4x washers Ø 10.5 mm to DIN 125; 2x flat gaskets made of PTFE, max. permissible 420 bar, 80 °C Flange connection with M10 screws only permissible up to PN 160.	K16	F) <b>7MF9411-6BB</b>
Accessory set to EN (connection between valve manifold and pressure transmitter)	l/ac	C) 7M50444 5DD
4x screws <sup>7</sup> / <sub>16</sub> -20 UNF x 1¾ inch to ASME B18.2.1; chromized steel 2x flat gaskets made of PTFE, max. permissible 420 bar, 80 °C	K36	F) <b>7MF9411-5DB</b>
Mounting bracket		
required <b>for wall mounting</b> or for securing to mounting rack, with bolts for mounting on valve manifold  • for valve manifold 7MF9413-1D.  • for valve manifold 7MF9413-1E.	M17 M18	F) <b>7MF9006-6NA</b> F) <b>7MF9006-6PA</b>
	0	1) 7 mil 3000-01 A
required <b>for mounting on 2" stand- pipe</b> , with bolts for mounting on valve manifold		
<ul> <li>for valve manifold 7MF9413-1D.</li> </ul>	M19	F) <b>7MF9006-6QA</b>
Mounting clip		
2 off, to secure mounting bracket to pipe	M16	F) <b>7MF9006-6KA</b>
Valve manifold 100 bar suitable for oxygen		
• for valve manifold 7MF9413-1D.	S13	
• for valve manifold 7MF9413-1E.	S14	
<ul> <li>When ordering accessory set or mounting together with the multiway cock, please use Order code; otherwise use Order No.</li> <li>Flange connections to DIN 19213 only permissible up to 160!</li> </ul>		
F) Subject to export regulations AL: 91999, ECCN: N.		

Order No.

Selection and Ordering data