Selection and Ordering Data

Description

Analyzer part Measuring cell

O-ring (set of 10)

Fusible plug (device fuse)

Front plate without LCD display

Electronics

1 2						
Motherboard, with firmware	X	Х	×	_	1	
Adapter board, LCD/keyboard	X	X		1	1	
LC display (non-Ex version)	X			1	1	
Line transformer, 115 V	X	X	X	_	1	
Line transformer, 230 V	X	X	Х	_	1	
Connector filter	X	X	X	_	1	
Fusible plug, T 0.63/250 V	X	X		2	4	
Fusible plug, 1 A, 110/120 V	X	X	Х	2	4	
D) Subject to AL export regulations: 91999, ECCN: N						

7MA2521

Χ

Χ

Χ

W75041-E5602-K2 W79054-L1010-T630 W79054-L1011-T100 E) Subject to AL export regulations: 91999, ECCN: EAR99H

7MB2511 Ex

Х

Х

Х

7MB2511

Х

Х

2 years

(aty)

5 years

(qty)

2

D)

D)

D)

D)

D)

D)

Order No.

A5E00095332

A5E00124182

A5E00061505

C79165-A3042-B508

C79451-A3474-B601 C79451-A3474-B605 W75025-B5001-B1

W75040-B21-D80 W75040-B31-D80

If the CALOMAT 6 is supplied with a specially cleaned gas path for high oxygen context ("Cleaned for O₂ service"), please ensure that you specify this when ordering. This is the only way to guarantee that the gas path will continue to comply with the special requirements for this version.